

YUEXIN TYRE CATALOGUE

KEERUN TIRE CO., LTD.

This version is applied for BACH HO PCS., LTD; VIETNAM only



With special design and compound for only use of trailer or semi-trailer.

All these tyres in these catalogue cannot be used for lorries truck and buses.



YX111



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
12R22.5	18PR	17.0	300	1085	9.00	3550/3250	152/149	L	930
11R22.5	18PR	14.5	272	1042	8.25	3250/3000	149/146	L	930

**This product cannot be used for lorries truck and buses.*



YX858



Suitable for only trailer or semi-trailer on mid-short distance transportation of paved road and mixed road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
12.00R20	20PR	18.5	306	1121	8.50	4000/3650	156/153	K	900

**This product cannot be used for lorries truck and buses.*



YX608



Suitable for only trailer or semi-trailer on mid-short distance transportation of paved road and mixed road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
11R22.5	16PR	16.0	274	1050	8.25	3000/2725	146/143	M	830
12R22.5	18PR	18.0	296	1086	9.00	3550/3250	152/149	L	930
11R22.5	18PR	16.0	274	1050	8.25	3250/3000	149/146	M	830
315/80R22.5	20PR	16.0	312	1076	9.00	4625/4125	161/157	L	900
10.00R20	18PR	17.5	270	1048	7.50	3250/3000	149/146	K	930
11.00R20	18PR	16.5	288	1083	8.00	3550/3250	152/149	K	930
12.00R20	20PR	16.5	308	1118	8.50	4000/3650	156/153	K	900

**This product cannot be used for lorries truck and buses.*



YX616



Suitable for only trailer or semi-trailer on mid-short distance transportation of paved road and mixed road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
11R22.5	16PR	15.0	279	1054	8.25	3000/2725	146/143	M	930
12R22.5	18PR	15.5	304	1078	9.00	3550/3250	152/149	K	930
315/80R22.5	20PR	15.0	306	1070	9.00	4125/3750	157/154	K	900
10.00R20	18PR	16.0	270	1046	7.50	3250/3000	149/146	K	930
11.00R20	18PR	17.0	288	1083	8.00	3550/3250	152/149	K	930
12.00R20	20PR	17.5	310	1119	8.50	4000/3650	156/153	K	900

**This product cannot be used for lorries truck and buses.*



YX333



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
12R22.5	18PR	18.0	300	1085	9.00	3550/3250	152/149	L	930

**This product cannot be used for lorries truck and buses.*



YX668



Suitable for only trailer or semi-trailer on long-haul distance transportation of paved road.

Size	Ply Rating	Tread Depth (mm)	Section Width (mm)	Overall Diameter (mm)	Standard Rim (inch)	Load Single/Dual (kg)	Load Index	Speed Rate	Air Pressure (kPa)
385/65R22.5	20PR	16.5	390	1070	11.75	4500	160	K	900
11R22.5	18PR	17.0	279	1054	8.25	3250/3000	149/146	L	930
12R22.5	18PR	18.0	296	1083	9.00	3550/3250	152/149	L	930
11.00R20	18PR	16.5	288	1083	8.00	3550/3250	152/149	K	930

**This product cannot be used for lorries truck and buses.*



KEERUN TIRE (DEZHOU) CO., LTD
NO.399, NORTH KAIYUAN WEAT AVENUE, LELING CITY,
DEZHOU CITY,SHANDONG PROVINCE,CHINA North

KEERUN TIRE(RIZHAO) CO., LTD
GAOZE TOWN, WULIAN COUNTY, RIZHAO CITY,
SHANDONG PROVINCE, CHINA

<https://www.keeruntire.net>